



## Typical Chemical Characteristics

---

### Product:

**LSDO GL-5** “Limited Slip Differential Oil” SAE 90

### Description:

#### EN:

Special gear oil with high specification level API: GL-5, which is suitable for all the differential gear boxes (Limited Slip Differential). It is absolute recommended for race cars and for off road **4X4** automobiles.

#### EL:

Ειδικό λιπαντικό υψηλής αντοχής κατασκευασμένο για χρήση σε μπλοκέ διαφορικά (περιορισμένης ολίσθησης - Limited Slip Differential). Είναι κατάλληλο για αγωνιστική χρήση αλλά και για παντός τύπου εκτός δρόμου **4X4** οχήματα.

#### BG:

Специално трансмисионно масло, отговарящо на спецификацията API: GL-5, подходящо за скоростни кутии с диференциал с ограничено приплъзване. Силно препоръчително за състезателни автомобили, както и за автомобили **4x4**.

#### SR:

Specijalno menjacko ulje visokog API nivoa kvaliteta GL-5, pogodno za sve menjace sa diferencijalom. Takođe se preporučuje i trkackim i off road **4X4** automobilima.

#### DE:

Spezielles Getriebeöl auf hoher API-Spezifikationsstufe: GL-5, geeignet für alle Differentialgetriebe (Ausgleichsgetriebe mit begrenztem Schlupf). Absolut empfohlen für Rennautos und **4x4** Geländeautos.

#### RU:

Специальное трансмиссионное масло с высоким уровнем спецификации API: GL-5, благодаря чему подходит для всех дифференциальных коробок передач (с самоблокирующимся дифференциалом). Это лучший выбор для внедорожных гоночных автомобилей с полным приводом.

**Disclaimer:** The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.



## Typical Chemical Characteristics

### Characteristics:

Property	Method	Unit	Result
Specific Gravity 15°C	ASTM D 1298	kg/L	0,885
Viscosity at 100°C	ASTM D 445	cSt	13,5 – 24,0
Viscosity Index	-	-	>105
Pour Point	ASTM D 97	°C	<15
Flash Point	ASTM D 92	°C	>180
Color	-	-	Crystal gold

### Specifications:

API: GL-5  
 MIL-L-2105D,  
 ZF TE ML 05/C  
 & Ford M2C-105A

**Disclaimer:** The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.