



Typical Chemical Characteristics

Product:

MGL-4 SAE 85W-140, 80W-90, 90 & 80W

Description:

EN:

Gear oil with high viscosity index basic oils and high quality additives. Designed to have properties against degeneration caused by friction. Recommended for cogwheels and motion transmission lubrication.

EL:

Υψηλής ποιότητας λιπαντικά για οδοντωτά γρανάζια κιβωτίων ταχυτήτων. Είναι ενισχυμένο με ειδικά πρόσθετα ώστε να εξαλείφει την τριβή και να παρουσιάζει αντοχή από την οξείδωση. Προτείνεται για χρήση σε αρκετά συστήματα μετάδοσης κίνησης.

DE:

Getriebeöl aus Grundölen mit hohem Viskositätsindex und Additiven hoher Qualität. Entwickelt zum Schutz vor Reibungsschäden. Empfohlen für die Schmierung von Zahnrädern und Bewegungsübertragung.

RU:

Трансмиссионное масло, изготовленное из базовых масел с высоким индексом вязкости с добавлением высококачественных присадок. Разработано с целью придания свойств защиты от ухудшения свойств из-за трения. Рекомендуется для смазывания зубчатых колес и трансмиссии.

BG:

Трансмисионно масло с висок вискозитетен индекс и висококачествени добавки. Създадено да предпазва елементите от разрушаване при триене. Препоръчва се за смазване на зъбни колелета.

SR:

Menjacko ulje sastavljeno od bazicnih ulja velike viskoznosti sa kvalitetnim aditivima. Posebno dizajnirano da pruža otpornost na habanje usled trenja. Preporučuje se za podmazivanje velikih prenosnih zupčanika.

Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.



Typical Chemical Characteristics

Characteristics:

Property	Method	Unit	85W-140	80W-90	90W	80W
Specific Gravity 15°C	ASTM D 1298	kg/L	0,885	0,877	0,879	0,871
Viscosity at 100°C	ASTM D 445	cSt	24,0 - 41,0	13,5 - 24,0	13,5 - 24,0	7,0 - 11,0
Viscosity Index	-	-	>125	>120	>115	>110
Pour Point	ASTM D 97	°C	<15	<18	<17	<18
Flash Point	ASTM D 92	°C	>220	>195	>190	>190
Color	-	-	Crystal gold	Crystal gold	Crystal gold	Crystal gold
Max °C @ 150.000mPa * s	-	°C	-12	-26	-	-26

Specifications:

API: GL-4

Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.