



## Typical Chemical Characteristics

---

### Product:

## Agron UTTO

### Description:

EN:  
Universal Transmission Tractor Oil (**U.T.T.O.**) especially formulated for new generation and for older generation, of agricultural and forestry machineries. This universal oil is for use in hydraulic, in transmission, in differential and in wet brakes systems.

EL:  
Νέο ευρείας χρήσης λιπαντικό (**U.T.T.O.**) για νέας αλλά και παλαιότερης τεχνολογίας αγροτικών ή δασικών μηχανημάτων. Αυτό το λιπαντικό προτείνεται για χρήση στο υδραυλικό σύστημα, στο σύστημα μετάδοσης κίνησης, στο σύστημα διαφορικού αλλά και επίσης στο σύστημα υδραυλικής πέδησης.

DE:  
Universelles Traktor-Getriebeöl (**U.T.T.O.**) speziell entwickelt für die neue Traktorgeneration, aber auch geeignet für Traktoren der älteren Generationen. Dieses universelle Öl eignet sich für Hydraulik- und Getriebesysteme, für Differentialbremssysteme und feuchte Bremssysteme. Der Gebrauch als Motoröl ist jedoch nicht empfohlen.

RU:  
Универсальное трансмиссионное масло «Universal Transmission Tractor Oil» (**U.T.T.O.**) предназначено специально для тракторов нового поколения, но может также использоваться и в более старых моделях. Это универсальное масло подходит для гидравлических и трансмиссионных систем, дифференциалов и тормозных систем мокрого типа. Не рекомендуется для использования в качестве моторного масла.

**Disclaimer:** The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although RS200 motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and RS200 motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.



## Typical Chemical Characteristics

### Characteristics:

Property	Method	Unit	10W-30/80W/ISO 68	20W-30/85W/ISO 100
Specific Gravity 15°C	ASTM D 1298	kg/L	0,888	0,890
Viscosity at 100°C	ASTM D 445	cSt	9,3 - 11,0	11,0 - 12,5
Viscosity Index	-	-	>130	>130
Pour Point	ASTM D 97	°C	<-25	<-23
Flash Point	ASTM D 92	°C	>210	>210
Total Base Number	ASTM D 2896	mgKOH/g	>10,5	>10,5
Color	-	-	Crystal gold	Crystal gold
Cold Cranking Simulator	ASTM D 5293	mPa-s	<3500 @ -20°C	<4500 @ -10°C

### Specifications:

API: GL-4  
 John Deere J20C, Allison C-4,  
 Ford M2C 134D,  
 DIN 51524-3 Part III HVLP,  
 Case New Holland MAT 3525 & 3526,  
 Massey Ferguson CMS M1135, M1141, M1143 & M1145  
 & ZF TE ML 06A/06B/06C/07B

**Disclaimer:** The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although RS200 motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and RS200 motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.