



TCC (Typical Chemical Characteristics)

MULTI SAE 20W-50, 15W-40, 50 & 40

Description:

EN:
Economical lubricant which offers high protection against wear and also offers high lubrication in gasoline or in diesel engines of classic cars.

EL:
Πρωτογενές λιπαντικό για κινητήρες κλασικών ιστορικών οχημάτων που αποτελείται από υψηλής ποιότητας συστατικά για να προσφέρει τέλεια λειτουργία σε κάθε βενζινοκινητήρα ή πετρελαιοκινητήρα.

DE :
Schmiermittel aus hochraffinierten Grundölen auf Paraffinbasis mit erstklassigen Additiven für perfekte Schmierung und optimalen Schutz von Benzin- und sogar Dieselmotoren vor Verschleiß und Oxidation.

FR:
Lubrifiant économique qui propose une protection élevée contre l'usure et offre également une grande lubrification à l'essence ou au diesel, de voitures classiques.

RU:
Минеральное моторное масло, на основе высокоочищенного минерального базового масла. Надёжно защищает двигатель при экстремально тяжёлых условиях эксплуатации, обеспечивает высокую смазку в бензиновых и дизельных двигателях, классических автомобилей.

Characteristics:

Property	Method	Unit	20W-50	15W-40	50	40
Specific Gravity 15°C	ASTM D 1298	kg/L	0,880 - 0,890	0,875 - 0,885	0,880 - 0,890	0,875 - 0,885
Viscosity at 100°C	ASTM D 445	cSt	16,3 - 21,9	12,5 - 16,3	16,3 - 21,9	12,5 - 16,3
Viscosity Index	-	-	>125	>120	>115	>110
Pour Point	ASTM D 97	°C	<-23	<-26	<-10	<-10
Flash Point	ASTM D 92	°C	>218	>210	>218	>215
Color	-	-	Crystal gold	Crystal gold	Crystal gold	Crystal gold

RS Laboratory: 07.12.2022

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece (EU) - website: rs200motoroil.com



Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.



TCC (Typical Chemical Characteristics)

MULTI SAE 20W-50, 15W-40, 50 & 40

Specification:

SAE 15W-40

API: SF / CF

1L	4L	5L	6L	7L	18L	204L
371154017	371154047	371154057	371154067	371154077	371154187	371154247

SAE 20W-50

API: SF / CF

1L	4L	5L	6L	7L	18L	204L
371205017	371205047	371205057	371205067	371205077	371205187	371205247

SAE 50

API: SF / CF

1L	4L	5L	6L	7L	18L	204L
371005017	371005047	371005057	371005067	371005077	371005187	371005247

SAE 40

API: SF / CF

1L	4L	5L	6L	7L	18L	204L
371005017	371005047	371005057	371005067	371005077	371005187	371005247

Package:

12x1L Carton / 6x4L Carton / 4x5L Carton / 3x6L Carton / 3x7L Carton / 1x18L Pail / 1x204L Drum



RS Laboratory: 07.12.2022

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece (EU) - website: rs200motoroil.com



Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.