



## TCC (Typical Chemical Characteristics)

LSDO SAE 80W-90

### Description:

EN:  
Special gear oil with high specification level API: GL-5, which is suitable for all the differential gear boxes (Limited Slip Differential). It is absolute recommended for race cars and for off road **4X4** automobiles.

EL:  
Ειδικό λιπαντικό υψηλής αντοχής κατασκευασμένο για χρήση σε μπλοκέ διαφορικά (περιορισμένης ολίσθησης - Limited Slip Differential). Είναι κατάλληλο για αγωνιστική χρήση αλλά και για παντός τύπου εκτός δρόμου **4X4** οχήματα.

DE:  
Spezielles Getriebeöl auf hoher API-Spezifikationsstufe: GL-5, geeignet für alle Differentialgetriebe (Ausgleichsgetriebe mit begrenztem Schlupf). Absolut empfohlen für Rennautos und **4x4** Geländeaautos.

FR:  
Huile spéciale pour engrenages haut de gamme de niveau API: GL-5, appropriée pour toute boîte de vitesse différentielle (différentiel à glissement limité). Absolument recommandée pour voitures de course et pour voitures 4X4 hors route.

BG:  
Специално трансмисионно масло, отговарящо на спецификацията API: GL-5, подходящо за скоростни кутии с диференциал с ограничено приплъзване. Силно препоръчително за състезателни автомобили, както и за автомобили **4x4**.

SR:  
Specijalno menjacko ulje visokog API nivoa kvaliteta GL-5, pogodno za sve menjace sa diferencijalom. Takotte se preporucuje i trkackim i off road **4X4** automobilima.

RU:  
Специальное трансмиссионное масло с высоким уровнем спецификации API: GL-5, благодаря чему подходит для всех дифференциальных коробок передач (с самоблокирующимся дифференциалом). Это лучший выбор для внедорожных гоночных автомобилей с полным приводом.

RS Laboratory: 02.01.2023

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece (EU) - website: [rs200motoroil.com](http://rs200motoroil.com)



**Disclaimer:** The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.



## TCC (Typical Chemical Characteristics)

LSDO SAE 80W-90

### Characteristics:

Property	Method	Unit	Result
Specific Gravity 15°C	ASTM D 1298	kg/L	0,885
Viscosity at 100°C	ASTM D 445	cSt	13,5 - 18,5
Viscosity Index	-	-	>105
Pour Point	ASTM D 97	°C	<25
Flash Point	ASTM D 92	°C	>180
Color	-	-	Crystal gold
Brookfield @ -26C	ASTM D 2983	mPa * s	<150.000

### Specifications:

API: GL-5 & MT-1,

SAE J2360, Scania STO 1:0,

Ford M2C-105A, MIL-L-2105E &

ZF TE ML 05A / 05C / 12A / 12C / 12E / 19B

1L	60L	204L
<b>675809017</b>	<b>675809607</b>	<b>675809247</b>

### Package:

12x1L Carton / 1x60L Mini-Drum / 1x204L Drum



RS Laboratory: 02.01.2023

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece (EU) - website: [rs200motoroil.com](http://rs200motoroil.com)



**Disclaimer:** The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.