



## TCC (Typical Chemical Characteristics)

Anax 4006 SAE 5W-40, 5W-30, 0W-30 & 0W-20

### Characteristics:

EN:

Fully synthetic oil with **Ultra Low SAPS** technology for diesel or gasoline engines, equipped with **DPF** or **TWC** emission reduction catalyts. It protects the exhaust emission systems and also the engine for long drain performance.

EL:

Πλήρες συνθετικό λιπαντικό με τεχνολογία "**Ultra Low SAPS**", για νέας γενιάς κινητήρες πετρελαίου ή βενζίνης με καταλύτες μείωσης ρύπων τύπου "**DPF** ή **TWC**". Προστατεύει και προσφέρει μακροζωία στο σύστημα του καταλύτη και επίσης στον κινητήρα.

DE:

Vollsynthetisches Öl der **Ultra Low SAPS** Technologie für Diesel- oder Benzinmotoren, welche mit **DPF**- oder **TWC**-Katalysatoren zur Emissionsminderung ausgestattet sind. Schützt die Abgasanlage und den Motor für lange Ölwechselintervalle bei Topleistung.

FR:

Huile entièrement synthétique de technologie "**Ultra Low SAPS**" pour les moteurs diesel ou à essence, équipés de **DPF** ou **TWC** catalyseurs de réduction des émissions. Elle protège les systèmes d'émission de gaz d'échappement et la protection de moteur pour des performances de vidange longue.

RU:

Полностью синтетическое масло, изготовленное по технологии **Ultra Low SAPS** (пониженного содержания сульфатной зольности, фосфора и серы) и предназначенное для дизельных или бензиновых двигателей, оснащенных сажевыми фильтрами или трехкомпонентными катализаторами для сокращения уровня выбросов. Защищает системы выхлопных газов, а также обеспечивает защиту двигателя без необходимости частой замены.

RS Laboratory: 21.11.2022

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece (EU) - website: [rs200motoroil.com](http://rs200motoroil.com)



**Disclaimer:** The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.



## TCC (Typical Chemical Characteristics)

Anax 4006 SAE 5W-40, 5W-30, 0W-30 & 0W-20

### Characteristics:

Property	Method	Unit	5W-40	5W-30	0W-40	0W-30	0W-20
Specific Gravity 15°C	ASTM D 1298	kg/L	0,855	0,85	0,80	0,80	0,78
Viscosity at 100°C	ASTM D 445	cSt	12,5 - 16,3	9,3 - 12,5	12,5 - 16,3	9,3 - 12,5	5,6 - 9,3
Viscosity Index	-	-	>130	>130	>140	>140	>140
Pour Point	ASTM D 97	°C	<-30	<-30	<-40	<-40	<-40
Flash Point	ASTM D 92	°C	>195	>192	>200	>200	>200
Total Base Number	ASTM D 2896	mgKOH/g	>6,5	>6,5	>6,5	>6,5	>6,5
Color	-	-	Crystal gold	Crystal gold	Crystal gold	Crystal gold	Crystal gold
Cold Cranking Simulator	ASTM D 5293	mPa-s	<6600 @ -30°C	<6600 @ -30°C	<6200 @ -35°C	<6200 @ -35°C	<6200 @ -35°C

### Specifications:

#### SAE 5W-40:

ACEA: C3, API: SP / SN Plus, MB 229.31 / 229.51 / 229.52, BMW Longlife-04, Opel OV0401547 & Renault RNO700 / RNO710

1L	5L	60L
446054017	446054057	446054607

#### SAE 5W-30:

ACEA: C2 (A7/B7 & A5/B5), API: SP RC / ILSAC GF-6 / SP / SN plus, MB 227.61 / 229.61 & Renault RNO700

1L	5L	60L
446053017	446053057	446053607

#### SAE 0W-40:

ACEA: C3, API: SP, MB 229.51 / 229.52 & Renault RNO700 / RNO710

1L	5L	60L
446004017	446004057	446004607

RS Laboratory: 21.11.2022

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece (EU) - website: [rs200motoroil.com](http://rs200motoroil.com)



**Disclaimer:** The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.



## TCC (Typical Chemical Characteristics)

**Anax 4006 SAE 5W-40, 5W-30, 0W-30 & 0W-20**

### SAE 0W-30:

ACEA: C2 (A5/B5), API: SP RC / ILSAC GF-6 / SP / SN plus, MB 227.61 / 229.61, BMW Longlife-12 FE & Ford WSS-M2C950-A

1L	5L	60L
446003017	446003057	446003607

### SAE 0W-20:

ACEA: C6 (C5), API: SP / SN plus, MB 229.71, Ford WSS-M2C950-A1, STJLR.03.5006, Opel OVO401547 & GM (Meets Dexos D criteria)

1L	5L	60L
446002017	446002057	446002607

### Package:

12x1L Carton / 4x5L Carton / 1x60L Mini-Drum



RS Laboratory: 21.11.2022

© copyright RS200 motor oil - Papantoniou S.A. - Industrial Zone of Lakkoma - Halkidiki - Greece (EU) - website: [rs200motoroil.com](http://rs200motoroil.com)



**Disclaimer:** The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.